

Servo Automatic Circle Punching Machine 380V 50HZ Numerical Control

Basic Information

Place of Origin: Guangdong, ChinaBrand Name: Jin Hongxiang

Certification: CE
Model Number: JQ2-6MM
Minimum Order Quantity: 1 set
Price: Negotiable

Packaging Details: Export wooden case
 Delivery Time: 5-10 days or negotiatio
 Supply Ability: 100 Sets per Month



Product Specification

• Function: Make A Circle Or Arc

Control System:
 PLC Display Screen, Servo Motor

• Applicable Industries: Lampshade, Fan Net Cover, Commodity

Shelf, Flower Rack,

Wire Size: ø2-6mmWarranty: 1 Year

Advantage: High Effecient Simple Operation

Port: Shenzhen ,ChinaControl: Numerical ControlVoltage: 380V/50HZ

Highlight: Servo Circle Punching Machine,

380V Circle Punching Machine, 50HZ Automatic Punching Machine



Automatic circle beating machine Servo circle beating machine

summarv

- 1. Servo motor feeding, fast speed, high accuracy, and the circle forming accuracy is within plus or minus 0.2mm. And the workpiece is stable for a long time. There are about 50 circles with a diameter of 200 mm per minute.
- 2. Hydraulic cutting, strong force and neat incision. Precision machining, special treatment of mechanical shaft, high precision, high toughness.
- 3. PLC programming, human-machine interface display, simple circle input, easy operation, easy to learn, very humanized.

Performance characteristics

1. Servo feeding - fast and accurate, speed adjustable. Oil pressure cut-off - large force, easy and powerful line cutting.



2. PLC programming + man-machine interface display, easy to operate and learn. High end servo + planetary reducer.



3. Precision CNC turning and milling. Gear, shaft, wire feeding wheel and other finishing, special hardening, surface grinding and polishing, high hardness, smooth and wear-resistant.



送线轮 光洁,耐磨,多线槽,精加工 wire feeding wheel is smooth, wear-resistant, multi trunking and finish machining

4. Omron encoder, high pulse, accurate feeding and fast response.



Technical parameters of servo circle machine

JQ2-6MM Technical parameters of servo circle machine

Wire diameter range Hard wire2-4 MM,Flexible cord2-6MM

Servo device:1KW+5B Hydraulic device:1.5KW

Maximum wire feeding speed:70M/S Circle diameter range:50-800M/S Circle diameter error: ±0.3MM


axles:2

Overall dimension:145*75*142CM

input voltage:380V50HZ

It is widely used in all walks of life, especially in the lighting industr

Sample display circle





Dongguan Jinghongxiang Automation Equipment Co., Ltd.

13925780098

jhx16888@gmail.com

wire-bendingmachine.com

No. 78, Shangzhong Road, Shangdi Industrial Zone, Liaobu Town, Dongguan, Guangdong, China