

# Automatic Flat Iron Metal Ring Making Machine Numerical Control For Lampshade

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Supply Ability:
- JQ2-10MM 1 set Negotiable

Guangdong, China

Jin Hongxiang

CE

- Export wooden case
- 5-10 days or negotiatio
- 100 Sets per Month



### **Product Specification**

- Function:
- Flat Iron Ring Punching • Control System: PLC Display Screen, Servo Motor Lampshade, Fan Net Cover, Commodity • Applicable Industries: Shelf, Flower Rack, • Wire Size: ø2-10mm • Warranty: 1 Year High Effecient Simple Operation Advantage: • Control: Numerical Control • Voltage: 380V/50HZ Highlight: Flat Iron Metal Ring Making Machine, Lampshade Metal Ring Making Machine

**Our Product Introduction** 

#### **Product Description**

#### Full automatic looping machine for lampshade products

Alias:

flat iron servo circle making machine, square iron fast circle making machine, barrel hoop circle making machine, stove circle making machine, I ampshade circle making machine, special-shaped material circle making machine, lampshade looping circle making machine, looping machine

This type of looping machine is customized, and it needs to lift the standard drawing or physical object of the product. Customized as required.

Double head punching cylinder, punching faster.

Servo feeding is fast and accurate, hydraulic cutting, cutting iron wire more forcefully **Performance characteristics** 

1. Servo feeding - fast and accurate, speed adjustable. Oil pressure cut-off - large force, easy and powerful line cutting.



2. PLC programming + man-machine interface display, easy to operate and learn. High end servo + planetary reducer.



3. Precision CNC turning and milling. Gear, shaft, wire feeding wheel and other finishing, special hardening, surface grinding and polishing, high hardness, smooth and wear-resistant.



送线轮 光洁, 耐磨, 多线槽, 精加工 wire feeding wheel is smooth, wear-resistant, multi trunking and finish machining



4. Omron encoder, high pulse, accurate feeding and fast response.



Technical parameters of servo circle machine

Model	JQ2-6MM	JQ2-8MM	JQ2-10MM
Wire diameter range (MM)	Hard wire2-4 lexible cord2- 6	Hard wire2-6 Flexible cord2- 8	Hard wire2-8 Flexible cord2- 10
Servo device	1KW+5B	1.5KW+5B	2.3KW+10B
Hydraulic device	1.5KW	2.2KW	2.2KW
Maximum wire feeding speed(M/MIN)	70	60	50
Circle diameter range (MM)	50-800	50-800	50-800
Circle diameter Tolerance MM	±0.3	±0.3	±0.3
Axis	2	2	4
Dimension(CM)	145*75*142	145*75*142	175*75*142

Multi function looping machine, widely used, can be used as long as it is a flat iron circle or a flat iron circular arc

Convenient setting, automatic counting, punching cylinder can be one cylinder or two cylinders according to needs





jhx16888@gmail.com

@ wire-bendingmachine.com

No. 78, Shangzhong Road, Shangdi Industrial Zone, Liaobu Town, Dongguan, Guangdong, China