

# 80m/Min Automatic Wire Bending Machine 8mm CNC Wire Butt Welder For Iron Wire

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Supply Ability:

J2-6
1 set
Negotiable
Export safety wooden case
5-10 days or negotiation
50 Set/Sets per Month

Guangdong, China Jin Hongxiang

CE



### **Product Specification**

Product Name:	2D Bending Wire Butt Welding Machine
Machine Type:	Fully Automatic
Core Components:	Spring Machine System, Precision Servo, CNC Machining
Warranty:	1 Year
Control System:	Servo + Spring Machine System + Precision Control Current Electric Box
Number Axes:	4
Maximum Wire Speed:	80M/min
• Feature:	It Is Fully Automatic, Which Can Bend The Line And The Butt Welding Machine After Bending The Frame, And It Can Be Completed At One Time.
• Wire Delivery Accuracy:	±0.1mm
Input Power:	380V,50/60HZ
• Port:	Shenzhen,China
Liabliabte	00m/min Automatic Mine Danding Mashina



#### **Product Description**

#### Automatic Wire Bending Butt Welding Machine for iron wire 2-8MM


Alias: Bending machine, bending and butt welding machine, bending frame + butt welding machine, 2D bending machine, 2D folding frame machine, **Product Description** 

#### \*Features

1. Automatic bending machine, servo high speed bending and butt welding machine

2.Bent frame + butt welding, it is a molding machine, can bend frame, can bend other 2D shape, all molding machine function has.

3.It can also be butt welded. For the products that need interface, it can directly form butt welding, which is more efficient, labor-saving and more humanized.



### Technical parameter

Model	J2DDH2-6MM	J2DDH2-8MM	J2DDH-Y-2-8MM
Number axes	4	4	3
Processing line diameter(MM)	Hard wire ø2-4	Hard wire ø2-6	Hard wire ø2-8
	Flexible cord ø2-6	Flexible cord ø2-8	Flexible cord ø2-10
Number of delivery wheels (Group)	3	3	3

Control system	32-bit high- performance processor, can store 2048 files, programming accuracy 0.01	32-bit high- performance processor, can store 2048 files, programming accuracy 0.01	32-bit high-performance processor, can store 2048 files, programming accuracy 0.01
Maximum wire speed(M/MIN)	80	70	60
Movement direction	rotating die can be raised and lowered, and the positive and negative motion can be realized	rotating die can be raised and lowered, and the positive and negative motion can be realized	rotating die can be raised and lowered, and the positive and negative motion can be realized
Wire delivery accuracy(mm)	±0.1	±0.1	±0.1
Power of butt welding transformer	water-cooling 50KVA	water-cooling 60KVA	water-cooling 50KVA
Solenoid valve and quantity	Taiwan Air TAC 15	Taiwan Air TAC 15	Taiwan Air TAC 12
Input power	380V,50/60HZ	380V,50/60HZ	380V,50/60HZ

**J** Dongguan Jinghongxiang Automation Equipment Co., Ltd.

**(** 13925780098

jhx16888@gmail.com (e) wire-bendingmachine.com

No. 78, Shangzhong Road, Shangdi Industrial Zone, Liaobu Town, Dongguan, Guangdong, China