

# 6mm 3D Wire Forming Machine Automatic Remote Control CE

#### **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- · Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

#### JX3D2-6 1 set

20 Set/Sets per Month

Guangdong, China

Jin Hongxiang

CE

- consult
  - Export wooden case
- 5-10 days or negotiation
- L/C, T/T



### **Product Specification**

- Product Name:
- Machine Type:
- Control System:
- Applicable Industries:
- · Warranty Of Core Components:
- Wire Size:
- No. Of Axis:
- Highlight:
- Automation:
- Port:
- Highlight:

3D PLC+servo Hardware, wire Processing 1 Year

3D Wire Bending Machine

- ø2-6mm
- 7 Axis
- 3D Wire Bending Machine
- Automatic
- Shenzhen
  - 6mm 3D Wire Forming Machine, 3D Wire Forming Machine CE



**Our Product Introduction** 

## **3D Wire forming machine**

This 3D molding machine is for iron wire with a diameter of 2-6mm

The biggest feature of this machine is that the iron wire rotates and the head is fixed

Performance characteristics

1. The computer starts and shuts down quickly, and the operation is simple and convenient. The computer interface can change the program while adjusting speed while producing.

2. High brand high-speed motor and reducer are used in configuration, and the production speed is more than 25% higher than that of similar products in domestic peers.

3. The production can realize that the angle does not change at the slowest angle, and the production stability is better.

4. Bearings, gears and other important parts are imported brand accessories, with a 365 day warranty, and the equipment is durable and reliable.

5. With high precision, it can be used for wire rod forming products in the range of 2.0-10 mm wire diameter, and the error is reduced to 0.1 mm 6. The matching use of steel wire butt joint machine makes the wire change operation of the machine more convenient.

7. It can be connected to the Internet and WiFi through mobile phone or computer to realize remote control, which makes after-sales service more convenient.

#### **Technical Parameters**


Model	JX3D-6	JX3D-8	JX3D-10
No. of axis	380V,7 axis	380V,7 axis	380V,7 axis
Machining wire diameter(MM)	Hard material Φ2.0 Φ4.0	Hard material Ф3.0 Ф6.0	Hard materialΦ3.0 Φ8.0
	Soft material $\Phi 2.0  \Phi 6.0$	Soft material \$43.0 \$\$.0	Soft materialΦ3.0 Φ10.0
Number of wire feeding wheels	3 groups	3 groups	3 groups
Spool servo motor (KW)	2	2.7	4.5
Head shaft servo motor (KW)	2	2.7	4.5
Cutter shaft servo motor(KW)	1	1	2
Lifting shaft servo motor (KW)	1	1	2
Angle axis servo motor (KW)	1	1	1
Machine size (MM)	3800X1860X1660	3800X1860X1660	3800X1860X1660

1. Computer control,

A. adopt speed closed-loop control; The maximum pulse frequency can reach 2MHz.



3D bending product display



No. 78, Shangzhong Road, Shangdi Industrial Zone, Liaobu Town, Dongguan, Guangdong, China